

## **MODEL** 75370

## **DESCRIPTION** 1/2" Multi-Purpose Chain Tie-Down System

COMPLETE ASSEMBLY PART NO. 75370 (CHAIN AND ANCHOR) 1/2" CLEVIS T-HOOK PART NO. 75384 ADJUSTABLE GRAB HOOK PART NO. 61209 COMPLETE CHAIN ASSEMBLY PART NO. 75390 12' 3" CLOSED 12' 9" OPEN - MAXIMUM (NO ANCHOR) CLAW HOOK PART NO. \$\$30982350 COMPRESSION UNIT PART NO. 74702 TELESCOPING LOAD BINDER PART NO. 75341 10p-90} SWIVEL ANCHOR PART NO. 75360

- AAR Approved
- Patent Pending

# LOAD SECUREMENT/ CHAIN TIE DOWN

## **MODEL** 75370

# **DESCRIPTION** 1/2" Multi-Purpose Chain Tie-Down System

Application: Used in conjunction with the tie-down channel on flat cars for securing all sizes of vehicles and equipment. This product replaces all standard 1/2" and 3/8" chain assemblies for rail cars.

#### CHAIN COMPONENT DESCRIPTION

#### HOLLAND PART NO.

• 1/2" Multi-Purpose Chain tie-down assembly with telescoping load binder, swivel anchor, compression unit, claw hook, adjustable grab hook, and clevis T-hook	75370
Chain tie-down assembly same as above, minus the swivel anchor	75390
Swivel Anchor (includes clevis pin and retaining pin for connecting	75360
to chain assembly)	
Telescoping Load Binder	75341
Compression Unit (field replaceable kit)	74702
Claw Hook	SS30982350
Adjustable Grab Hook	61209
<ul> <li>1/2" Clevis T-Hook (kit – includes clevis pin and retaining pin for connecting to chain)</li> </ul>	75384

### **OPTIONAL ACCESSORIES**

• Locking Ratchet Wrench

SS30980210

<sup>\*</sup>This chain assembly meets the 55,000 lbs. minimum breaking strength per AAR requirements.